


LD Series

5-100 kN Materials Testing



Specifications



A	Standard Machine Height	1728 mm / 68 in
	Extended Machine Height	2363 mm / 93 in
B	Standard Crosshead Travel	1070 mm / 42 in
	Extended Crosshead Travel	1669 mm / 65.7 in

Force Capacity	
LD5	5 kN / 1124 lbf
LD10	10 kN / 2248 lbf
LD30	30 kN / 6744 lbf
LD50	50 kN / 11240 lbf
LD100	100 kN / 22480 lbf

Crosshead Speed Range	
LD5	0.0001 to 1270 mm/min / 0.000004 to 50 in/min
LD10	0.0001 to 1270 mm/min / 0.000004 to 50 in/min
LD30	0.0001 to 1000 mm/min / 0.000004 to 40 in/min
LD50	0.0001 to 500 mm/min / 0.000004 to 20 in/min
LD100	0.0001 to 250 mm/min / 0.000004 to 10 in/min

Return Speed	
LD5	1270 mm/min / 50 in/min
LD10	1270 mm/min / 50 in/min
LD30	1000 mm/min / 40 in/min
LD50	650 mm/min / 26 in/min
LD100	325 mm/min / 10 in/min

Speed Accuracy	
0.1%	

Crosshead Travel	
Standard Height	1070 mm / 42 in
Extended Height	1669 mm / 65.7 in

The LD100 is available in only a standard height version.

Width Between Columns	
452 mm / 17.8 in	

Extension Resolution	
LD5/10	0.000354 µm per encoder count
LD30	0.000214 µm per encoder count
LD50	0.000121 µm per encoder count
LD100	0.000063 µm per encoder count

µm = micron.

Load Cell	
Load Cell Accuracy	< ± 0.5% of reading down to 1/100 of load cell capacity
Resolution	32-bit A/D converter
Min. Load Resolution	1 part in 10 ⁹

Extensometer Inputs	
Analog and Digital	

Data Transfer Rate to PC	
1 kHz	

Supply Voltage	
207-253 VAC at 50 Hz or 103.5-126.5 VAC at 60 Hz	

Load Measuring System	
EN ISO 7500-1:2015 Class 0.5 ASTM E4	

Software	
NEXYGENPlus 4	

Weight	
225 kg / 496 lb	

Operating Temperature	
10 to 40° C / 50 to 104° F	

Control Modes	
Position, Load Rate, and Strain Rate control	

LD Series Accessories Ordering Information

Part Number	Description
01/5041	LD Tablet with mount assembly, USB cable and cable management kit
01/5042	NEXYGEN <i>Plus</i> and LD Tablet with mounting arm assembly, USB cable and cable management kit
40/0783	NEXYGEN <i>Plus</i> 4 Software (optional)

LD Series Ordering Information

Order Number	Description
LD	LD Series
	Model
5	5 kN / 1124 lbf
10	10 kN / 2248 lbf
30	30 kN / 6744 lbf
50	50kN / 11240 lbf
100	100 kN / 22480 lbf
	Travel
S	Standard Travel
E	Extended Travel
P	Standard Travel POGO Design*
X	Extended Travel POGO Design**
	Operation
H	Hand-Held Remote
C	Main Console
	Power
115 V	US Power Cord
230 V	UK and Euro Power Cord
230V-CNAU	China and Australian Power Cord
	Sample Order Number
LD 50 E H 115V	LD Series 50kN model with Extended Travel, Hand-Held Remote and US Power Cord

* Our unique POGO system allows testing of very large samples with the added benefit of optional elevated and low temperature capability.

** The Extended Travel POGO is not available for the LD100 Model.

For detailed specifications go to the Data Sheet at ametektst.com

USA, Florida
Tel +1 (800) 527 9999
test.sales@ametek.com

India
Tel +91 22 2836 4750
test.sales@ametek.com

Singapore
Tel +65 6484 2388
test.sales@ametek.com

China, Shanghai
Tel +86 21 5886 5111
test.sales@ametek.com

China, Beijing
Tel +86 21 8526 2111-19
test.sales@ametek.com

United Kingdom
Tel +44 (0) 1243 833 370
test.sales@ametek.com

France
Tel +33 (0) 30 68 89 40
general.lloyd-instruments@ametek.fr

Germany
Tel +49 (0) 2159 9136 510
info.mct-de@ametek.de

Denmark
Tel +45 4816 8000
test.sales@ametek.com

LLOYD  TM
materials testing

No part of this document may be reproduced or modified in any form or by any means, electronic or mechanical, without express written permission from AMETEK STC.

©2020 AMETEK Incorporated

AMETEK[®]
SENSORS, TEST & CALIBRATION